

# TP2000

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 27-Nov-2012  
9317SP(cs)

CHEMWATCH 4772-36  
Version No:2.1.1.1  
CD 2012/4 Page 1 of 7

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

TP2000

### PRODUCT USE

■ Used according to manufacturer's directions.

### SUPPLIER


Company: ParexGroup Pty Ltd  
Address:  
67 Elizabeth Street  
Wetherill Park  
NSW, 2164  
Australia  
Telephone: +61 2 9616 3000  
Emergency Tel: **1800 039 008**  
Fax: +61 2 9725 5551  
Email: marketing@davco.com.au  
Website: www.davco.com.au

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.** According to the Criteria of NOHSC, and the ADG Code.

### CHEMWATCH HAZARD RATINGS



### RISK

#### Risk Codes

R33  
R34  
R41  
R20?  
R40(3)?  
R42/43?

#### Risk Phrases

- Danger of cumulative effects.
- Causes burns.
- Risk of serious damage to eyes.
- Inhalation may produce health damage\*.
- Limited evidence of a carcinogenic effect\*.
- Possible respiratory and skin sensitiser\*.

### SAFETY

#### Safety Codes

S01  
S22  
S24  
S25  
S36  
S37  
S39  
S51  
S09  
S401

#### Safety Phrases

- Keep locked up.
- Do not breathe dust.
- Avoid contact with skin.
- Avoid contact with eyes.
- Wear suitable protective clothing.
- Wear suitable gloves.
- Wear eye/face protection.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- To clean the floor and all objects contaminated by this material, use water and detergent.
- Take off immediately all contaminated clothing.
- In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
- In case of accident or if you feel unwell IMMEDIATELY contact Doctor or Poisons Information Centre (show label if possible).

S27  
S26

S45

continued...

# TP2000

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Nov-2012

9317SP(cs)

CHEMWATCH 4772-36

Version No:2.1.1.1

CD 2012/4 Page 2 of 7

Section 2 - HAZARDS IDENTIFICATION

S63

- In case of accident by inhalation: remove casualty to fresh air and keep at rest.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
cement		20-40
graded sand	14808-60-7.	20-40
fillers		20-40
ingredients at levels determined not to be hazardous		balance

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- - For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

### EYE

- If this product comes in contact with the eyes:
  - Immediately hold eyelids apart and flush the eye continuously with running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
  - Transport to hospital or doctor without delay.

### SKIN

- If skin or hair contact occurs:
  - Immediately flush body and clothes with large amounts of water, using safety shower if available.
  - Quickly remove all contaminated clothing, including footwear.
  - Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
  - Transport to hospital, or doctor.

### INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

### NOTES TO PHYSICIAN

- Treat symptomatically.

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

- - There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.

### FIRE/EXPLOSION HAZARD

- - Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions.
- Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air

continued...

# TP2000

## Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Nov-2012

9317SP(cs)

CHEMWATCH 4772-36

Version No:2.1.1.1

CD 2012/4 Page 3 of 7

### Section 5 - FIRE FIGHTING MEASURES

---

or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions).

- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion.

- In the same way as gases and vapours, dusts in the form of a cloud are only ignitable over a range of concentrations; in principle, the concepts of lower explosive limit (LEL) and upper explosive limit (UEL) are applicable to dust clouds but only the LEL is of practical use; - this is because of the inherent difficulty of achieving homogeneous dust clouds at high temperatures (for dusts the LEL is often called the "Minimum Explosible Concentration", MEC).

Combustion products include: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), silicon dioxide (SiO<sub>2</sub>), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

#### FIRE INCOMPATIBILITY

■ - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

#### HAZCHEM

None

---

### Section 6 - ACCIDENTAL RELEASE MEASURES

---

#### MINOR SPILLS

- - Remove all ignition sources.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

#### MAJOR SPILLS

- Moderate hazard.
- CAUTION: Advise personnel in area.
- Alert Emergency Services and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

---

### Section 7 - HANDLING AND STORAGE

---

#### PROCEDURE FOR HANDLING

- - Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)
- Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame.
- Establish good housekeeping practices.
- Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.

#### SUITABLE CONTAINER

- - Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

#### STORAGE INCOMPATIBILITY

- - Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.
- Avoid contact with copper, aluminium and their alloys.
- Avoid reaction with oxidising agents.

#### STORAGE REQUIREMENTS

- - Store in original containers.

continued...

# TP2000

## Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Nov-2012

9317SP(cs)

CHEMWATCH 4772-36

Version No:2.1.1.1

CD 2012/4 Page 4 of 7

Section 7 - HANDLING AND STORAGE

- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

The following materials had no OELs on our records

- graded sand:

CAS:14808- 60- 7

### MATERIAL DATA

TP2000:

- for calcium silicate:

containing no asbestos and <1% crystalline silica

ES TWA: 10 mg/m<sup>3</sup> inspirable dust

TLV TWA: 10 mg/m<sup>3</sup> total dust (synthetic nonfibrous) A4

Although in vitro studies indicate that calcium silicate is more toxic than substances described as "nuisance dusts" is thought that adverse health effects which might occur following exposure to 10-20 mg/m<sup>3</sup> are likely to be minimal. The TLV-TWA is thought to be protective against the physical risk of eye and upper respiratory tract irritation in workers and to prevent interference with vision and deposition of particulate in the eyes, ears, nose and mouth.

NOTE: This substance has been classified by the ACGIH as A4 NOT classifiable as causing Cancer in humans.

For calcium carbonate:

The TLV-TWA is thought to be protective against the significant risk of physical irritation associated with exposure.

The concentration of dust, for application of respirable dust limits, is to be determined from the fraction that penetrates a separator whose size collection efficiency is described by a cumulative log-normal function with a median aerodynamic diameter of 4.0 µm (+-) 0.3 µm and with a geometric standard deviation of 1.5 µm (+-) 0.1 µm, i.e..generally less than 5 µm.

GRADED SAND:

NOTE: This product contains negligible amount of respirable dust.

### PERSONAL PROTECTION

#### RESPIRATOR

- Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

#### EYE

- - Chemical goggles.

- Full face shield may be required for supplementary but never for primary protection of eyes

- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

#### HANDS/FEET

- NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene
- nitrile rubber
- butyl rubber
- fluorocautchouc.

#### OTHER

- - Overalls.
- P.V.C. apron.

continued...

# TP2000

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Nov-2012

9317SP(cs)

CHEMWATCH 4772-36

Version No:2.1.1.1

CD 2012/4 Page 5 of 7

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Barrier cream.
- Skin cleansing cream.

### ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

White powder with a characteristic odour; not miscible with water.

### PHYSICAL PROPERTIES

Does not mix with water.

Sinks in water.

State	Divided Solid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Applicable	Viscosity	Not Applicable
Boiling Range (°C)	Not Applicable	Solubility in water (g/L)	Immiscible
Flash Point (°C)	Not Applicable	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Applicable
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	>1
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Applicable
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Applicable

## Section 10 - STABILITY AND REACTIVITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

■ - Presence of incompatible materials.

- Product is considered stable.

- Hazardous polymerisation will not occur.

*For incompatible materials - refer to Section 7 - Handling and Storage.*

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.

Not normally a hazard due to the physical form of product. The material is a physical irritant to the gastro-intestinal tract.

##### EYE

■ The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.

If applied to the eyes, this material causes severe eye damage.

##### SKIN

■ The material can produce chemical burns following direct contact with the skin.

Handling wet cement can cause dermatitis. Cement when wet is quite alkaline and this alkali action on the skin contributes strongly to cement contact dermatitis since it may cause drying and defatting of the skin which is followed by hardening, cracking, lesions developing, possible infections of lesions and penetration by soluble salts.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

continued...

# TP2000

## Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Nov-2012

9317SP(cs)

CHEMWATCH 4772-36

Version No:2.1.1.1

CD 2012/4 Page 6 of 7

### Section 11 - TOXICOLOGICAL INFORMATION

#### INHALED

■ Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.

Effects on lungs are significantly enhanced in the presence of respirable particles.

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

#### CHRONIC HEALTH EFFECTS

■ Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

Red blood cells and rabbit alveolar macrophages exposed to calcium silicate insulation materials in vitro showed haemolysis in one study but not in another. Both studies showed the substance to be more cytotoxic than titanium dioxide but less toxic than asbestos.

Cement contact dermatitis (CCD) may occur when contact shows an allergic response, which may progress to sensitisation.

Sensitisation is due to soluble chromates (chromate compounds) present in trace amounts in some cements and cement products.

Overexposure to respirable dust may cause coughing, wheezing, difficulty in breathing and impaired lung function. Chronic symptoms may include decreased vital lung capacity, chest infections

Repeated exposures, in an occupational setting, to high levels of fine-divided dusts may produce a condition known as pneumoconiosis which is the lodgement of any inhaled dusts in the lung irrespective of the effect.

#### TOXICITY AND IRRITATION

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

#### CARCINOGEN

graded sand

International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs

Group

1

### Section 12 - ECOLOGICAL INFORMATION

No data

#### Ecotoxicity

Ingredient

Persistence:  
Water/Soil

Persistence: Air

Bioaccumulation

Mobility

graded sand

No Data  
Available

No Data  
Available

No Data  
Available

No Data  
Available

### Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.

- DO NOT allow wash water from cleaning or process equipment to enter drains.

- It may be necessary to collect all wash water for treatment before disposal.

- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

- Where in doubt contact the responsible authority.

- Recycle wherever possible.

- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

continued...

# TP2000

Chemwatch Independent Material Safety Data Sheet

Issue Date: 27-Nov-2012

9317SP(cs)

CHEMWATCH 4772-36

Version No:2.1.1.1

CD 2012/4 Page 7 of 7

Section 13 - DISPOSAL CONSIDERATIONS

- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material)
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

## Section 14 - TRANSPORTATION INFORMATION

**HAZCHEM:**

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

## Section 15 - REGULATORY INFORMATION

**Indications of Danger:**

C Corrosive

POISONS SCHEDULE None

**REGULATIONS**

**Regulations for ingredients**

**graded sand (CAS: 14808-60-7) is found on the following regulatory lists;**

"Australia - New South Wales Hazardous Substances Prohibited for Specific Uses", "Australia - New South Wales Hazardous Substances Requiring Health Surveillance", "Australia - Queensland Workplace Health and Safety Regulation - Hazardous substances for which health surveillance must be supplied", "Australia Australian Safety and Compensation Council (ASCC) Draft National Code of Practice for the Control of Workplace Hazardous Chemicals - Schedule 4 Hazardous chemicals Requiring Health Surveillance", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 - Hazardous Substances Requiring Health Surveillance", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals (other than lead) requiring health monitoring", "Australia Work Health and Safety Regulations 2011 - Restricted hazardous chemicals", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments"

**portland cement (CAS: 65997-15-1) is found on the following regulatory lists;**

"Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)"

**No data for TP2000 (CW: 4772-36)**

## Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 27-Nov-2012

Print Date: 27-Nov-2012

*This is the end of the MSDS.*